



Part Number: 8618

Audio/Control/Instrumentation, (3) 16 AWG (19X29) TC, PE/PVC, Foil Shld

[Request Sample](#)

Product Description

Three 16 AWG stranded (19x29) tinned copper conductors, conductors cabled, polyethylene insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
16	19x29	TC - Tinned Copper	3

Conductor Count:	3
Conductor Size:	16 AWG

Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.0315 in

Color Chart

Number	Color
1	Black
2	Red
3	Clear

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum/Polyester	Beldfoil® (Z-Fold®)	100 %	TC - Tinned Copper	18	16x30 mm

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.327 in	0.031 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
4.8 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
26 pF/ft	50 pF/ft

Shielding:	Foil(s) or Copper Tape(s)
------------	---------------------------

Current

Max. Recommended Current [A]
7 Amps per conductor @ 25°C

Voltage

UL Description	UL Voltage Rating
AWM Style 2107	600 V RMS

CL3	300 V RMS
-----	-----------

Temperature Range

UL Temp Rating:	80°C (UL AWM Style 20253)
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	60 lbs/1000ft
Max Recommended Pulling Tension:	110 lbs
Min Bend Radius/Minor Axis:	3.5 in

Standards

NEC Articles:	800
NEC/(UL) Specification:	CL3
UL AWM Style:	UL Style 20253 (600 V 80°C)
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
8618 0601000	Chrome	C
8618 060500	Chrome	C
8618 0605000	Chrome	
8618 060U500	Chrome	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.