

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - new logo 2011

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

H

-

P

LTR

DESCRIPTION

DATE

DWN

APVD

A

ECR-16-015010

24OCT2016

KR

MvE

NOTES:

1 CONNECTOR ACCEPTS MULTIPLE WIRES SIZES: SEE TABLE.

2 HOUSING AND BUTTON MATERIAL : POLYCARBONATE

3 IDC CONTACT MATERIAL: PhBR

4 PRINTING LOGO'S: KEMA, PARTNUMBER, TE, DATE CODE, WIRE SIZE, IP CLASS.

5 WIRE INSULATION DIAMETER RANGE IS FROM 1.75 TO 2.85 mm

BUTTON COLOR	HOUSING COLOR	PARTNUMBER	DESCRIPTION	CABLE SIZE
BLUE	CLEAR	2213800-4	SPLICING CONNECTOR SEALED	AWG 20 (0.52mm ²) / AWG 22 (0.33mm ²)
GREEN		2213800-3	SPLICING CONNECTOR UNSEALED	AWG 20 (0.52mm ²) / AWG 22 (0.33mm ²)
BLUE		2213800-2	SPLICING CONNECTOR SEALED	AWG 18 (0.82mm ²) TO 0.75mm ²
GREEN		2213800-1	SPLICING CONNECTOR UNSEALED	AWG 18 (0.82mm ²) TO 0.75mm ²

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 22DEC2015

RAGHAVENDRA.K

CHK 22DEC2015

M.V.ESSSEN

APVD 22DEC2015

O.L.F.JUNSE

PRODUCT SPEC

108-133061

APPLICATION SPEC

114-133061

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME

N.S.COOLSPLICE

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-2213800

-

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC

±

1 PLC

±0.2

2 PLC

±0.15

3 PLC

±

4 PLC

±

ANGLES

±3°

FINISH

SEE NOTES

MATERIAL

SEE NOTES

SEE NOTES

SCALE 2:1

SHEET 1

OF 1

REV A

1470-19 (3/11)