


## Housing - HC-HV 3-KML-73/M1PG16 - 1773695

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Coupling housing, with single locking latch, height 52 mm, with screw connection, 1x Pg16



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 115739
Weight per Piece (excluding packing)	231.91 GRM
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### Dimensions

Height	73 mm
Width	43 mm
Length	73 mm
Wrench size, union nut	22 mm
External cable diameter	7.5 mm ... 15 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Note	For contact inserts HV-HV3
Design	HV3
Housing type	Coupling housings

# Housing - HC-HV 3-KML-73/M1PG16 - 1773695

## Technical data

### General

Locking type	With single locking latch
No. of cable exits	1
Cable exit	Straight
Screw connection	With
Type of the screw connection	1x Pg16
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Cable gland material	Nickel-plated brass
Cable seal material	NBR
Material lock	High-grade steel
Material grip body interlock	PA-GF

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209

### ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

## Approvals

### Approvals

# Housing - HC-HV 3-KML-73/M1PG16 - 1773695

## Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

## Approval details



## Drawings

Dimensioned drawing

