

CABLE-D25SUB/B/S/100/KONFEK/S


Order No.: 2302133

The illustration shows a 15-position version



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2302133>

Round shielded cable set, with 25-pos. D-SUB female and male connectors, cable length: 1 m

| Commercial data | |
|--------------------------|--|
| GTIN (EAN) |  |
| sales group | I682 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Catalog page information | Page 270 (IF-2009) |

Product notes

WEEE/RoHS-compliant since:
11/15/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

| General | |
|---|----------------------|
| Nominal voltage U_N | 125 V AC/DC |
| Max. current carrying capacity per path | 2 A |
| Max. conductor resistance | $\leq 0.09 \Omega/m$ |
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

| | |
|------------------------------------|--|
| Number of positions | 25 |
| Number of positions, control side | 25 |
| Number of connectors, control side | 1 |
| Number of positions, module side | 25 |
| Number of connectors, modul side | 1 |
| Fixed cable length | 1 m |
| Single wire, cross section | 0.25 mm ² |
| AWG | 24 |
| External diameter | 10.5 mm |
| Shielding | yes |
| | Tinned copper-braided shield, approx. 85% covering |
| Insertion/withdrawal cycles | > 200 |

Certificates / Approvals



Certification

CUL, GOST, UL

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;