

UBK 2-PE-24-HB


Discontinued item

Order No.: 2807900

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2807900>

DIN rail module with two-stage surge protection for a floating double conductor. Self-contacting grounding foot for mounting on NS 32 or NS 35/7.5, version: 24 V AC/DC.

Commercial data

GTIN (EAN)	 4 017918 075385
Note	Made-to-order
sales group	J422
Pack	10 pcs.
Customs tariff	85363010

Product notes

WEEE/RoHS-compliant since:
03/29/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Housing material	PA
Inflammability class acc. to UL 94	V2
Ambient temperature (operation)	-40 °C ... 60 °C
Degree of protection	IP20

Protective circuit

Nominal voltage U_N	24 V AC
Maximum continuous voltage U_c (wire-ground)	26.4 V AC
Nominal current I_N	300 mA (60 V DC)
Nominal discharge surge current I_n (8/20) μ s (Core-Earth)	10 kA
Max. discharge surge current I_{max} (8/20) μ s maximum (Core-Core)	214 A
Max. discharge surge current I_{max} (8/20) μ s maximum (Core-Earth)	10 kA
Output voltage limitation at 1 kV/ μ s (Core-Core) static	≤ 55 V
Output voltage limitation at 1 kV/ μ s (Core-Earth) static	≤ 450 V
Residual voltage at I_n , (conductor-conductor)	≤ 55 V
Response time t_A (Core-Core)	≤ 1 ns
Response time t_A (Core-Earth)	≤ 100 ns
Cut-off frequency f_g (3 dB), sym. in 50 Ohm system	6.2 MHz
Cut-off frequency f_g (3 dB), sym. in 150 Ohm system	2.2 MHz
Cut-off frequency f_g (3 dB), sym. in 600 Ohm system	550 kHz
Resistance in series	9.4 Ω

Connection data

Stripping length	8 mm
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Certificates / Approvals



Certification

GOST

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;