

Adapter cable - CABLE- 9/8/250/RSM/LENZE - 2981826

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Cable adapter for PSR speed monitors (PSR-RSM4 and PSR-MOTIONSTOP), 9/8-pos., cable length: 2.5 m, for controller: Lenze



Version for Siemens, Heidenhain control system is illustrated

Product Features

- Option to connect to PSR-RSM4 and PSR-MOTIONSTOP safe speed monitors
- Suitable for connection to the existing motor feedback interface of an electrical drive
- Controller type:LENZE
- 9-pos. D-SUB connection
- Length of connecting cable to speed monitor: 250 cm

Key Commercial Data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 160.0 g |
| Custom tariff number | 85444290 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--------------------|-------|
| Fixed cable length | 2.5 m |
|--------------------|-------|

Ambient conditions

| | |
|---|--|
| Ambient temperature (operation) | -20 °C ... 60 °C (for fixed installation) |
| | 0 °C ... 50 °C (for flexible installation) |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

General

| | |
|---------------------|-----------------------------|
| Connection 1 | To the device |
| Connection method | RJ45 |
| Number of positions | 8 |
| Connection method | D-SUB 9 plug/D-SUB 9 socket |

Adapter cable - CABLE- 9/8/250/RSM/LENZE - 2981826

Technical data

General

| | |
|-------------------------|--|
| Number of positions | 9 |
| Cable resistance | ≤ 260 Ω/km |
| Conductor material | Bare Cu litz wires |
| Shielding | Plastic-coated aluminum foil, tinned copper braided shield |
| | Soldering on D-SUB housing |
| Conductor cross section | 0.48 mm ² (AWG 26) |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27060307 |
| eCl@ss 4.1 | 27060307 |
| eCl@ss 5.0 | 27060307 |
| eCl@ss 5.1 | 27060307 |
| eCl@ss 6.0 | 27060307 |
| eCl@ss 7.0 | 27060307 |
| eCl@ss 8.0 | 27149290 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001449 |
| ETIM 3.0 | EC001449 |
| ETIM 4.0 | EC000467 |
| ETIM 5.0 | EC002783 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211901 |
| UNSPSC 7.0901 | 39121501 |
| UNSPSC 11 | 39121501 |
| UNSPSC 12.01 | 39121501 |
| UNSPSC 13.2 | 39121501 |

Approvals

Approvals

Approvals

EAC

Adapter cable - CABLE- 9/8/250/RSM/LENZE - 2981826

Approvals

Ex Approvals

Approvals submitted

Approval details

| |
|-----|
| EAC |
|-----|
