

## Specification Sheet

Part Number: 211-60001



P-Clip, 0.39" Wide, 0.20" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS, Black, 100/pkg

|                                |  |
|--------------------------------|--|
| <b>Article Number</b>          | 211-60001  |
| <b>Type</b>                    | H2P  |
| <b>Color</b>                   | Black (BK)   |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• P-Clamps easily guide and locate wire and cables up to 1" in diameter.</li><li>• Designed with a radius edge to prevent chafing and cutting into insulation.</li></ul> |
| <b>Quantity Per</b>            | bag  |
| <b>Product Description</b>     | HellermannTyton P-Clamps easily guide and locate wires and cables. The clamps are designed with a radius edges to prevent chafing and cutting into insulation. Available sizes up to 1" bundle diameters.      |
| <b>Short Description</b>       | P-Clip, 0.39" Wide, 0.20" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS, Black, 100/pkg  |

Global Part Name

H2P-PA66HS-BK

Fixation Method

screw-hole

Variant

Closed

Width W (Imperial)

0.39

Width W (Metric)

10.0

Bundle Diameter Max (Imperial)

0.20

Bundle Diameter Max (Metric)

5.0

Nominal Diameter (Imperial)

3/16

Nominal Diameter (Metric)

5.0

Wall Thickness WT (Imperial)

0.039

Wall Thickness WT (Metric)

1.0

Mounting Hole Diameter D (Imperial)

0.17

Mounting Hole Diameter D (Metric)

4.2 mm

Mounting Hole Diameter D Min (Imperial)

0.17

Mounting Hole Diameter D Max (Imperial)

0.17

Mounting Hole Diameter D Max (Metric)

4.2

Mounting Hole Centers (Imperial)

0.37

|                                       |  |
|---------------------------------------|--|
| <b>Material</b>                       | Polyamide 6.6 heat stabilized (PA66HS) |
| <b>Material Shortcut</b>              | PA66HS                                 |
| <b>Flammability</b>                   | UL 94 V2                               |
| <b>UV Resistant (Yes/No)</b>          | No                                     |
| <b>Operating Temperature (Metric)</b> | -40°F to +221°F (-40°C to +105°C)      |
| <b>Reach Complaint(Article 33)</b>    | Yes                                    |
| <b>ROHS Complaint</b>                 | Yes                                    |
| <b>Package Quantity(Imperial)</b>     | 100                                    |
| <b>Package Quantity (Metric)</b>      | 100                                    |
| <b>Customs Number</b>                 | 3926909987                             |
| <b>Content Unit(BMEcat)</b>           | pcs.                                   |
| <b>Weight (Metric)</b>                | 0.4                                    |

