

Planar Cores (7898400321)



Part Number: 7898400321

98 PLANAR EI CORE SET

Planar EE and EI cores, with their low profile are suitable for board level installation allowing assembly without the need for plastic coilformers and can also allow windings integrated into multi- level PCBs. Planar ER cores with their low mass and low profile are suitable for Surface Mount installations in low power filter and transformer applications.

Planar EE, ER and EI cores can be supplied with the center post gapped to a mechanical dimension, or an A_L value.

Weight: 10.5 (g)

| Dim | mm | mm tol | nominal inch | inch misc. |
|-----|------|--------|--------------|--------------------------|
| A | 21.8 | ± 0.40 | 0.858 | <input type="checkbox"/> |
| B | 5.7 | ± 0.15 | 0.224 | <input type="checkbox"/> |
| C | 15.8 | ± 0.35 | 0.622 | <input type="checkbox"/> |
| D | 3.2 | ± 0.15 | 0.126 | <input type="checkbox"/> |
| E | 16.8 | ± 0.40 | 0.661 | <input type="checkbox"/> |
| F | 5 | ± 0.20 | 0.197 | <input type="checkbox"/> |
| G | 2.5 | ± 0.15 | 0.098 | <input type="checkbox"/> |

Chart Legend

$\Sigma l / A$: Core Constant, l_e : Effective Path Length, A_e : Effective Cross- Sectional Area, V_e : Effective Core Volume
 A_L : Inductance Factor

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

| Electrical Properties | |
|------------------------------------|-----------|
| A_L (nH) | 5500 ±25% |
| A_e (cm ²) | 0.79 |
| $\Sigma l / A$ (cm ⁻¹) | 3.3 |
| l_e (cm) | 2.61 |
| V_e (cm ³) | 2.06 |
| A_{min} (cm ²) | 0.79 |

A_L value is measured at 1 kHz, B < 10 gauss.