


A




Extended length is with 500g of force

B

C

D



SEC: A-A

P1	P2
1	6
2	5
3	4
4	3
5	2
6	1

**Material:**

- Plug Housing: Polycarbonate, clear
- Plug Terminal: 0.36"[0.14MM] Thick Phosphor Bronze
- Connector: 50µ" of Selective Gold Contact Plating
  - Area, Gold flash over the remainder
  - Over 2.54µm[.000100] thick nickel underplate
- Conductor(X6C): 26AWG (0.12X12) Bare Copper
- Insulation(X6C): PP6331 ID 0.95-1.0
- Jacke: PVC No UL 80 P
- Package: Individual PE Bag

Extended Length ("L2")	Typical Retracted Length ("L1")
60.0 Inches - 69.0 Inches	21.5 Inches
1,524.0MM-1,752.6MM	546.1MM

F

G

Scale	1:1					Name	Item No.
TOLERANCE						Chappell	<b>AT-C-26-6/6/B-5</b>
X.X	±0.40				Drawn	11.02.11	
X.XX	±0.25				Approved		Title
X.XXX	±0.15						NON-UL 26AWG (0.12X12)*6C, O.D.: 2.4*6.8MM, Single Plug, 50µ" of contact plating, BLACK
Angle	±3°						Drawing No.
							rev00
							Replace
							Sheet



H