



Technical specification :

Rated voltage: IEC 61076-2-104	30 V
Current rating: IEC 61076-2-104	3 A at 40°C
Insulation resistance: IEC 60512	≥100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	≥100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Sealing:	FPM
Coupling nut:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:

Recommended torque:	0,4 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 9: 36-000210

Contact assignment:

- 1) brown
- 2) white
- 3) blue
- 4) black
- 5) grey

Part no:	Description:	Length L:	Cable:
42-11104	SAL - 8B - RK5.1 - 2 / A1	2m	PVC, grey, 5x0,25mm ² Cable: 781-A1250G
42-11105	SAL - 8B - RK5.1 - 3 / A1	3m	
42-11106	SAL - 8B - RK5.1 - 5 / A1	5m	
42-11107	SAL - 8B - RK5.1 - 10 / A1	10m	
42-xxxxx	SAL - 8B - RK5.1 - ... / A1	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: a 23.08.11 BCB Ä3941 data modified	dim. in mm	title: Female connector M8x1 axial, B-coding									
	tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%			<table border="1"> <tr> <td></td> <td>date</td> <td>name</td> </tr> <tr> <td>drawn</td> <td>04.08.10</td> <td>Fromm</td> </tr> <tr> <td>appd.</td> <td>04.08.10</td> <td>Mankopf</td> </tr> </table>		date	name	drawn	04.08.10	Fromm	appd.	04.08.10
		date		name								
	drawn	04.08.10		Fromm								
appd.	04.08.10	Mankopf										
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH		dwg no: 42K1A242										
		part no: see table										