



HAMMOND MANUFACTURING

1182F240
50/60Hz VA:80

PRI: 2x 117V BLK-WHT, BRN-ORN
SEC: 1x 240V @ 0.333A RED-BLU

1A0080A000A000240

MADE IN CANADA DATE PB

RoHS Compliant

CE, UL, RoHS symbols

SUPPLIED WITH: TWO 0.062" T X 2.50" OD RUBBER WASHERS.
ONE 18GA X 2.375" OD STEEL MOUNTING WASHER.
ONE 10-24 BOLT 2.00" LONG WITH A LOCK WASHER AND 10-24 HEX NUT.

ELECTRICAL DATA:		
TESTS	CONDITIONS	ACCEPTANCE CRITERIA
Sec. N.L.V	@ 117V, 60Hz	
	BLK & BRN to WHT & ORN	
OR	@ 234V, 50Hz	
	BLK to ORN (Connect BRN & WHT)	
	RED - BLU	263.84 V ±2%
POLARITY	BLK, BRN and RED.	ADDITIVE
DCR	BLK - WHT	11.840 Ohms ±20%
IN OHMS	BRN - ORN	11.840 Ohms ±20%
	RED - BLU	30.400 Ohms ±20%
HIPOT	PRIMARY - SECONDARY	4000V, 60Hz, 1 SEC
	PRIMARY - PRIMARY	600V, 60Hz, 1 SEC

PROPERTY AND COPYRIGHT NOTICE

THIS DRAWING AND THE INFORMATION IT CONVEYS ARE THE PROPERTY OF HAMMOND MANUFACTURING. IT MAY NOT BE REPRODUCED, TRANSMITTED OR USED IN ANY MANNER WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF HAMMOND MANUFACTURING.

REV	NOTES	BY	DATE	ELECTRONIC DIVISION 52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5 PHONE: 519.886.6181 FAX: 519.886.9540	
1	UPDATED THE HARDWARE, WAS 8-32 X 1.75" LONG.	GG	15/04/14	TOROID POWER TRANSFORMER DRAWN: G. GRAY DATE: 21/03/2014 NUMBER: 1182F240 APPROVED: DATE:	