

# D-SUB pressure nut - VS-M20 (5-13) - 1652127

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



D-SUB cap nut with line seal, for conductor diameter of 5 mm ... 13 mm, for sleeve housing VS-25-...



## Key commercial data

Packing unit	1
Minimum order quantity	5
Catalog page	Page 441 (PC-2011)
GTIN	 4 017918 917111
Custom tariff number	39269097
Country of origin	GERMANY

## Technical data

### General data

Color	gray
Type of the screw connection	M20
External cable diameter	5 mm ... 13 mm
Degree of protection for housing	IP67
Ambient temperature (operation)	-40 °C ... 80 °C
Housing material	PA
Seal material	Neoprene
Inflammability class according to UL 94	V0

## Classifications

### eclass

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109

# D-SUB pressure nut - VS-M20 (5-13) - 1652127

## Classifications

### eclass

eCl@ss 7.0	27149109
------------	----------

### etim

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC002355

### unspsc

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

## Drawings

### Dimensioned drawing

