



Han® 3 A, Hybrid,
components device side
panel feed-throughs

Identification	Part number	Drawing	Dimensions in mm
<p>RJ45 female for direct device integration</p> <p>solder variant SMD 90° angled</p> <p>I</p>	<p>09 45 551 1100¹⁾ 09 45 551 1110²⁾</p>		<p>pcb layout</p>
<p>Power module with 4 contacts for direct device integration</p> <p>Reel with 100 pieces</p> <p>II</p>	<p>09 45 525 0040 09 45 525 0041</p>	<p>recommended PCB power layout (SMD) scale 4:1</p>	
<p>Housing bulkhead mounting separate incl. flat seal for direct device integration</p> <p>Plastic version, black Metal version Standard, grey Metal version M, black Metal version EMC, unpainted</p> <p>III</p>	<p>09 45 525 0021 10 12 005 1004 09 45 525 0027 09 45 525 0028</p>	<p>Dimensions valid for plastic version</p>	
<p>Panel feed-through set</p> <p>Plastic version, black, Cat. 5 Metal version Standard, grey, Cat. 5 Metal version M, black, Cat. 5 Metal version Standard, grey, Cat. 6 Metal version M, black, Cat. 6</p> <p>IV</p>	<p>09 45 225 1300 10 12 005 1002 09 45 215 1301 09 45 215 1760 09 45 215 1761</p>		
<p>Protection cover for panel feed-through IP65 / IP67</p> <p>Plastic version, black Metal version Standard, grey Metal version M, black</p>	<p>09 20 003 5449 09 20 003 5425 09 37 003 5405</p>		

1) Packaging: Blister à 120 pieces
2) Packaging: Tape & Reel à 130 pieces
Technical characteristics and general informations see page 04.15