



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: x.x=± 0.4mm
x.xx=± 0.25mm
3. RATING: DC 30V, 0.3A
4. OPERATING FORCE: 200± 100gf
5. TRAVEL: 3.3mm FULL TRAVEL
6. LIFE CYCLES: 10,000 CYCLES
7. OPERATING TEMPERATURE: -20°C TO 70°C
8. CONTACT RESISTANCE: 20mΩ MAX.
9. INSULATION RESISTANCE: 100MΩ MIN@ 500VDC.
- ▲ 10. LED COLOR: BLUE
11. ▲ DENOTES CRITICAL PARAMETER.
12. 2002/95/EC (RoHS) COMPLIANT.

LED SPECS	UNITS	BLUE
FORWARD CURRENT	mA	20
FORWARD VOLTAGE @20mA	V	3.3 TYP - 4.0 MAX
LUMINOUS INTENSITY @ 20mA	mcd	1300 TYP



REV	PCR NO	DESCRIPTION	DATE	BY
B	21534	CORRECT PCB LAYOUT, UPDATE DRAWING	8/4/14	EBP
A	19543	Release For Production	12/22/10	BMA

TITLE WBL2UOABQR05CLR				
SCALE	DATE	DR	DWG	REV
2:1	12/22/2010	BA	XB0927P	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED