



TERMINATION:

P1	P2	COLOR
1	1	BLACK
2	2	RED
3	3	GREEN
4	4	YELLOW

Extended Length ("L2")	Typical Retracted Length ("L1")
300.0 Inches - 345.0 Inches	75.0 Inches
7,620.0MM-8,763.0MM	1,905.0MM

Material:

- Plug Housing: Polycarbonate, clear
- Plug Terminal: 0.36"[0.14MM] Thick Phosphor Bronze
- Connector: 50 μ " of Selective Gold Contact Plating
 - Area, Gold flash over the remainder
 - Over 2.54 μ m[.000100] thick nickel underplate
- Conductor(X4C): 26AWG (0.12X12) Bare Copper
- Insulation(X4C): PP6331 ID 0.95-1.0
- Jacke: PVC No UL 80 P
- Package: Individual PE Bag

SEC:A-A

Scale	1:1					Name	Item No.	
TOLERANCE					Drawn	11.02.11	AT-C-26-4/4/B-25/R	
X.X	± 0.40				Approved	Chappell		
X.XX	± 0.25						Title NON-UL 26 AWG (0.12X12)*4C, O.D.: 2.4*4.8MM, Reverse Plug, 50 μ " of contact plating, BLACK	
X.XXX	± 0.15						Drawing No.	
Angle	$\pm 3^\circ$						rev00	
		Modification	Date	Name	ASSMANN W+SW components		Replace	
								Sheet

