

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	VOLTAGE		APPLICABLE CABLE	CABLE DIAMETER : $\phi 6.9 \pm 0.3$	
	CURRENT				
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
REMARK		APPROVED	AO. SUZUKI	09.05.07	
		CHECKED	KN. ICHIKAWA	09.05.07	
		DESIGNED	MO. SHIMOYAMA	09.05.07	
		DRAWN	MO. SHIMOYAMA	09.05.07	
Unless otherwise specified, refer to JIS C 5402.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-126674-00		
	SPECIFICATION SHEET	PART NO.	DH-27-CMB (6. 9)		
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0036-9-00		1/1