

# 3M™ Lapping Films 562X and 566X

## Product Description

3M™ Lapping Films 562X and 566X are 0.5 micron Cerium Oxide mineral coated on 3.0 mil polyester film backing. They are used in lapping or polishing of various substrates.

## Key Features

- Produces excellent surface finish
- Reduces overall process time
- Helps produce high yields
- Non-slurry processing

## Mineral Size Grading Chart

Product ID	Mineral Size (nominal)	Backing	Color
562X (plain back)	0.5 micron	3.0 mil polyester	White
566X (PSA)	0.5 micron	3.0 mil polyester	White

## Converted Forms

Sheets, discs and rolls.

Maximum width: 26 inches

## Backing

Polyester film

Nominal thickness: 3.0 mil

## Storage and Shelf Life

The recommended product shelf life is 24 months from date of shipment from the manufacturing location when stored in the original product container and packaging materials and at 10-32°C (20-90°F) and 30-70% RH.

When stored in conditions as described above, the abrasive has not been shown to degrade with time.

## Regulatory

For regulatory information about this product, contact your 3M representative.

## Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

## Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

## Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

## Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



### Electronics Materials Solutions Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
1-800-251-8634 phone  
651-778-4244 fax  
[www.3M.com/electronics](http://www.3M.com/electronics)

3M is a trademark of 3M Company.  
Please recycle.  
© 3M 2014. All rights reserved.  
60-5002-0078-1

