

Specification Sheet

Part Number: 111-00732



High-Temp Cable Tie, 7.9" Long, 50lb Tensile Strength, ETFE, Blue, 100/pkg

Article Number	111-00732
Type	T50R
Color	Blue (BU)
Features & Benefits	<ul style="list-style-type: none">• ETFE cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure.• Inside serrations allows for strong hold on cables and wire bundles.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

ETFE ties provide excellent protection against radiation, ultraviolet light, and a wide range of chemicals. They are also rated for low outgassing applications. HellermannTyton's ETFE ties come in a standard color of blue for easy identification. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description

High-Temp Cable Tie, 7.9" Long, 50lb Tensile Strength, ETFE, Blue, 100/pkg

Global Part Name

T50R-E/TFE-BU

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

222.3

Length L (Imperial)

8.0

Length L (Metric)

201

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.19

Width W (Metric)

4.7

Bundle Diameter Min (Imperial)

0.2

Bundle Diameter Min (Metric) 5.0

Bundle Diameter Max (Imperial) 2.0

Bundle Diameter Max (Metric) 50.0

Thickness T (Imperial) 0.06

Thickness T (Metric) 1.5

Material Ethylenterafluoroethylene - (E/TFE)

Material Shortcut E/TFE

Flammability UL 94 V0

Operating Temperature (Metric) -112°F to +338°F (-80°C to +170°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB UL | ANSI/UL 62275 UL | ANSI/UL 1565

UL Recognized (US and Canada) Yes

Package Quantity(Imperial) 100

Package Quantity (Metric) 100

Customs Number

3926909987

Content Unit(BMEcat)

pcs.

Weight (Metric)

1.3