



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to 153QK000-000, DCA-00067752

Documents

Assembly instruction 53 T2
Panel piercing B 185

Material and plating

Connector parts

Center contact
Outer contact
Dielectric
Gasket

Material

Spring bronze
Brass
PTFE
Silicone

Plating

Gold, min. 0.15 µm, over chemical nickel
White bronze(e.g. Optalloy®)

Electrical data

Impedance	50 Ω
Frequency	DC to 11 GHz
Return loss	≥ 30 dB, DC to 2.5 GHz ≥ 27 dB, 2.5 to 4 GHz ≥ 20 dB, 4 to 6 GHz
Insertion loss	≤ 0.05 dB x √ f [GHz]
Insulation resistance	≥ 5 x10 ³ MΩ
Center contact resistance	≤ 1.5 mΩ
Outer contact resistance	≤ 1.5 mΩ
Test voltage	2500 V rms
Working voltage	1000 V rms
RF-leakage	≤ -90 dB @ 3 GHz
Intermodulation (3 rd order)	≤ -112 dBm @ 2 x 20 W

- Limitations are possible due to the used cable type

Mechanical data

Mating cycles	min. 100
Engagement force	30 N (typ.)
Disengagement force	30 N (typ.)

Environmental data

Temperature range	-40°C to +125°C
Thermal shock	MIL-STD-202, Meth. 107 D, Cond. B
Corrosion	MIL-STD-202, Meth. 101 D, Cond. B
Vibration	MIL-STD-202, Meth. 204 D, Cond. A
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture resistance	MIL-STD-202, Meth. 106 F
Degree of protection (mated pair)	IEC 60529, IP68 0.3 bar (interface only)
RoHS	compliant

Tooling

N/A

Suitable cables

UT 141 ; RG 402

Weight

Weight	20.8 g/pce
--------	------------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
A. Fellner	07/07/05	Sa. Krautenbacher	11.03.14	f00	14-0352	T. Krojer	11.03.14
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de		Page 2 / 2