

Power Strip - Agency-Approved Hospital/Medical Outlet Strip

MODEL NUMBER: **PS-615-HGULTRA**



Highlights

- Versatile power distribution strip
- 6 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- 15A resettable circuit breaker
- Double-fault safety protection

Package Includes

- PS-615-HGULTRA Power Strip
- User manual with warranty information

Description

Providing 15A capacity AC power distribution in a rugged all-metal outlet strip for 120V applications, Tripp Lite's PS-615-HGULTRA Power Strip is agency approved for use in physicians' offices, imaging centers, laboratories and medical facilities. Features include 6 hospital-grade receptacles with GFCI protection, 15-foot AC power cord and built-in resettable circuit breaker. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: Incorporates NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

Features

- Rugged all-metal housing withstands years of use without breakage
- 6 x NEMA 5-15R-HG hospital-grade output receptacles (2 with GFCI protection)
- 15-ft. AC cord with integrated, molded NEMA5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges.
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60Hz electrical compatibility
- Tested to UL (USA) and cUL (Canada)
- Agency approved for use in medical facilities

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332123268 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| OUTPUT | |
|--|--|
| Frequency Compatibility | 50 / 60 Hz |
| Circuit Breaker (amps) | 15 |
| Overload Protection | 15A circuit breaker |
| Outlet Orientation | Single row of 6 |
| INPUT | |
| Recommended Electrical Service | 15A 120V |
| Input Connection Type | NEMA 5-15P-HG |
| Input Cord Length (ft.) | 15 |
| Input Cord Length (m) | 4.57 |
| Voltage Compatibility (VAC) | 120 |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | No power switch |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 2.25 x 15.00 x 6.00 |
| Shipping Dimensions (hwd / cm) | 5.72 x 38.10 x 15.24 |
| Shipping Weight (lbs.) | 3.55 |
| Shipping Weight (kg) | 1.61 |
| Unit Dimensions (hwd / in.) | 1.5 x 13.75 x 2.5 |
| Unit Dimensions (hwd / cm) | 3.8 x 34.9 x 6.4 |
| Unit Weight (lbs.) | 2.4 |
| Unit Weight (kg) | 1.09 |
| Material of Construction | Metal |
| Integrated Keyhole Mounting Tabs | Keyhole tabs and flanges enable mounting to a variety of surfaces. Keyhole spacing 10.75" (26cm) center to center; 1.75" (4.4cm) center to edge of strip |
| Receptacle Color | White |
| Color (AC Line Cord) | White |
| CERTIFICATIONS | |
| UL1363 (Power Tap) | TUV tested to UL1363 |
| cUL / CSA (Canada) | TUV tested to CAN/CSA C22.2 No. 21-95 |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<https://www.tripplite.com/products/product-certification-agencies>