

Specification Sheet

Part Number: 596-00814



Solar Label, Printable, Spanish, PHOTOVOLTAIC DC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll

| | |
|---------------------|---|
| Article Number | 596-00814 |
| Type | DCDISCS |
| Color | Red (RD) |
| Features & Benefits | <ul style="list-style-type: none">• Made with UV-stable inks and materials for durability and weather resistance.• Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.• High abrasion and scuff resistance for high-performance labeling.• Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. |
| Quantity Per | roll |

Product Description

HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Printable, Spanish, PHOTOVOLTAIC DC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll

Global Part Name

DCDISCS-840/926-RD

Technical Description

Printable Solar Label, Spanish Version, PHOTOVOLTAIC DC DISCONNECT, 3.75" X 1.0", Red

Local Order Number 2

English Version: 596-00238

Width W (Imperial)

3.75

Width W (Metric)

92.25

Thickness T (Metric)

64.0

Height H (Imperial)

1.0

Height H (Metric)

25.4

Material

Type 840/926, Polyester (PET), UV stable, clear Polyester laminate

Material Shortcut

840/926

| | |
|--|-----------------------------------|
| Adhesive | Acrylic |
| Halogen free | No |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature (Metric) | -40°F to +302°F (-40°C to +150°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL 969 CSA 66956 |
| UL Recognized (US) | Yes |
| Package Quantity(Imperial) | 50 |
| Package Quantity (Metric) | 50 |
| Customs Number | 3919102055 |
| Labels per Column | 1 |
| Labels per Row | 1 |
| Weight (Metric) | 0.521 |
| Weight (Imperial) | 1.14 |

