


ITEM	CONNECTOR PART NO.	DESCRIPTION
1	SPND-001T-C0.5	PNI CONNECTOR - FEMALE CONTACT
2	SPNI-001T-P0.5	PNI CONNECTOR - MALE CONTACT
3	UL1061, 22 AWG	BLACK

Applicable Housings				
NO. OF CIRCUITS	PLUG HOUSING (FOR FEMALE CONTACT) PART NO.	SOCKET HOUSINGS (FOR MALE CONTACT)		OPTIONAL RETAINER
		WITHOUT PANEL LOCKS	WITH PANEL LOCKS	
2	PNIRP-02V-S	PNIRR-02VF	PNIRR-02V	PNIS-02V
3	PNIRP-03V-S	PNIRR-03VF	PNIRR-03V	PNIS-03V
4	PNIRP-04V-S	PNIRR-04VF	PNIRR-04V	PNIS-04V
5	PNIRP-05V-S	PNIRR-05VF	PNIRR-05V	PNIS-05V
6	PNIRP-06V-S	PNIRR-06VF	PNIRR-06V	PNIS-06V
8	PNIRP-08V-S	PNIRR-08VF	PNIRR-08V	PNIS-08V
10	PNIRP-10V-S	PNIRR-10VF	PNIRR-10V	PNIS-10V



**JST**

SCALE	1:1
DIMENSIONS	All dimensions are in MM with a tolerance of +/- 3.0 unless otherwise specified.
DRAWN BY	STEVEN PILKINGTON
CHECKED BY	JUSTIN BAKER

DESCRIPTION	2.0 mm Pitch PNI Series Standard Leads - 6" Inside Length DOUBLE-END LEADS, F-M
ASSEMBLY PART NO.	ASPNDSPNI22K152
DRAWING NO. & REVISION	GAM-242
DATE	4/6/2017

REV.	DESCRIPTION	DATE	BY