

## Specification Sheet

Part Number: T150M0UVX2



Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, PA66UV, Black, 25/pkg

Article Number	111-15660
Type	T150M
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• UV stabilized heavy-duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures .</li><li>• Head design provides high tensile strength with very low insertion force.</li></ul>
Quantity Per	bag

### Product Description

Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, PA66UV, Black, 25/pkg

**Global Part Name**

T150M-PA66UV-BK

**Minimum Tensile Strength (Imperial)**

175.0

**Minimum Tensile Strength (Metric)**

780.0

**Length L (Imperial)**

21.0

**Length L (Metric)**

530.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.35

**Width W (Metric)**

8.9

**Bundle Diameter Min (Imperial)**

0.32

**Bundle Diameter Min (Metric)**

8.0

**Bundle Diameter Max (Imperial)**

5.9

**Bundle Diameter Max (Metric)**

150.0

<b>Thickness T (Imperial)</b>	0.079
<b>Thickness T (Metric)</b>	2
<b>Material</b>	Polyamide 6.6 UV-resistant (PA66UV)
<b>Material Shortcut</b>	PA66UV
<b>Flammability</b>	UL 94 V2
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.

**Weight (Metric)**

8.4