

## Specification Sheet

Part Number: 151-10920



Q Mount, M4 Screw, 0.83" x 0.38" x 0.26", For Q18–Q50 ties, PA66, Natural, 100/bag

Article Number	151-10920
Type	CTQM5
Color	Natural (NA)
Features & Benefits	<ul style="list-style-type: none"><li>•2- or 4-way entry options for the Q-Tie, offering flexibility and stability</li><li>•Designed for use with 18- through 120-pound cable ties to provide stability when securing bundles.</li><li>•Secures with a single screw, providing quick installation.</li></ul>
Quantity Per	bag

### Product Description

Q-Series mounting bases are designed to work exclusively with the Q-Tie® cable tie series. This mounting component can be secured with screws. The Q-Mount allows either a two- or four-way entry for the Q-Tie, providing a quick and simple insertion into the mount. Once in place, the Q-Tie will not slip out, even in vertical mounting applications.

**Short Description**

Q Mount, M4 Screw, 0.83" x 0.38" x 0.26", For Q18–Q50 ties, PA66, Natural, 100/bag

**Global Part Name**

CTQM5-PA66-NA

**Length L (Imperial)**

0.83

**Length L (Metric)**

21.0

**Fixation Method**

Screw Mounting and Rivet

**Width W (Imperial)**

0.38

**Width W (Metric)**

9.5

**Height H (Imperial)**

0.26

**Height H (Metric)**

6.7

**Cable Tie Width Max (Imperial)**

0.2

**Cable Tie Width Max (Metric)**

5.0

**Mounting Hole Diameter D (Imperial)**

0.175

**Mounting Hole Diameter D (Metric)**

4.5 mm

**Mounting Hole Diameter D Min (Imperial)**

0.18

**Mounting Hole Diameter D Max (Metric)**

4.5

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL   ANSI/UL 62275 UL   ANSI/UL 1565 UL   ANSI/UL 746B
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.