



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS) MINIMUM
BF24438-33B	WHITE 10,000°k x = .283 y = .299	1400 TYP. @ 0°C 1820 MAX.	835	5.0		20,000
				6.5±5%	38,000±10%	

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>METRIC THIRD ANGLE PROJECTION</p>			<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 1.0 2 PL +/- 0.05 ANGLE +/- 0</p>		<p><b>JKL</b> COMPONENTS CORPORATION</p>					
					<p>TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP</p>					
<p>DRAWN BY L. WENGSTROM</p>			<p>APPVD BY DATE L.R. 7/30/09</p>		<p>SIZE <b>A</b></p>	<p>FSCM NO. <b>55335</b></p>	<p>DRAWING NO. <b>BF24438-33B</b></p>			
<p>APPVD DATE</p>			<p>- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED</p>		<p>SCALE NONE</p>	<p>RELEASED DATE 3/17/04</p>	<p>REVISION DATE 7/30/09</p>	<p>REV. NO. <b>A</b></p>	<p>SHEET 1 OF 1</p>	
<p>REV. NO.</p>	<p>DESCRIPTION/ECO NUMBER</p>	<p>APPVD DATE</p>								
<b>A</b>	RATED LIFE HRS MINIMUM	7/30/09								
	RELEASED	3/17/04								