

## Specification Sheet

Part Number: REZ300.NB3P



Releasable Cable Tie, 12" Long, 30 lb Tensile Strength, PA66, Black, 100/pkg

**Article Number**

115-40300

**Type**

REZ300

**Color**

Black (BK)

**Features & Benefits**

- The unique, patented head design enables the tie to be inserted through a standard style head for permanent locking or can be twisted into the pinch-releasable style head for easy opening at a later time.
- The quick pinch-release mechanism can be released by one hand even when the tie is under tension.

**Quantity Per**

bag

**Product Description**

HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Releasable Cable Tie, 12" Long, 30 lb Tensile Strength, PA66, Black, 100/pkg
<b>Global Part Name</b>	REZ300-PA66-BK
<b>Minimum Tensile Strength (Imperial)</b>	30.0
<b>Minimum Tensile Strength (Metric)</b>	135
<b>Length L (Imperial)</b>	12.0
<b>Length L (Metric)</b>	305
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	Yes
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.19
<b>Width W (Metric)</b>	4.7
<b>Bundle Diameter Min (Imperial)</b>	0.63
<b>Bundle Diameter Min (Metric)</b>	16.0
<b>Bundle Diameter Max (Imperial)</b>	3.2
<b>Bundle Diameter Max (Metric)</b>	80.0
<b>Thickness T (Imperial)</b>	0.055

**Thickness T (Metric)** 1.4

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL 94 V2

**Operating Temperature (Metric)** -40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909987

**Content Unit(BMEcat)** pcs.

**Weight (Metric)** 2.29

