


PCB-2214



19 PC-Kontaktbohrungen Ø1±0,1

Ansicht ist auf der Steckseite Stiffi-Stecker gezeichnet.

Fuer Steckseite Buchen-Stecker ist das Bohrbild spiegelbildlich zur Hauptachse (▼)

Fuer Winkelverdrehung sind die Koordinaten entsprechend umzurechnen

19 PC-contact-holes Ø1±0,1

View on mating face of pin-connector

For mating face of socket-connector the hole pattern is symmetrically to the main axis (▼)

For angular rotation the coordinates must be changed accordingly

Winkelverdrehung: W = 80°
angular rotations: Z = 280°



Bohrung / hole	Lage / position		Bohrung / hole	Lage / position	
	X-Achse / X-axis	Y-Achse / Y-axis		X-Achse / X-axis	Y-Achse / Y-axis
A	5,00	8,50	L	-5,00	8,50
B	7,50	4,25	M	0,00	8,50
C	9,95	0,00	N	2,50	4,25
D	7,50	-4,25	P	5,00	0,00
E	5,00	-8,50	R	2,50	-4,25
F	0,00	-8,50	S	-2,50	-4,25
G	-5,00	-8,50	T	-5,00	0,00
H	-7,50	-4,25	U	-2,50	4,25
J	-9,95	0,00	V	0,00	0,00
K	-7,50	4,25			

d1 HB	
Gehäuseform	shell type
CA 02L	CA 20L
3,4	4,5

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change
Drawings illustrate normal insulator positioning

Material Specification:

Shell Material: Aluminium alloy

Shell Plating: Olive drab chromate over cadmium (conductive)

Insulator Material: CR-Elastomere

Contact Material: Copper alloy

Contact Plating: Hard silver

all dimensions are in mm
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
CUSTOMER



Engineered for life

ITT CANNON GmbH
D - 71384 Weinstadt/Germany

description CA20L22-14P-B

Box mounting receptacle

PCB Ø 0,76 / Pin / Layout: 22-14

© All rights reserved. Reproduction or issue to third in any form
whatever is only permitted with written authorization of ITT Cannon



page
2/2

revision
1488 30. Jul 18