



- NOTES: (b)
- FOR WAVESOLDERING (SOLDER BATH TEMPERATURE 260°C FOR 5 SEC. AND SOLDER PREHEAT 100°C FOR 30 SEC.)
  - METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
  - INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0; BLACK
  - CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):  
 PLEASE ADD A for GOLD FLASH over NICKEL ( PREFERRED TYPE )  
 PLEASE ADD B for 20µm HARD GOLD over min. 50µm NICKEL  
 PLEASE ADD C for 30µm HARD GOLD over min. 50µm NICKEL  
 CONTACT TAILS PRETINNED
  - CAPACITANCE: 370pF ±20%
  - DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
  - P.C.B. HOLE DRILLINGS ON SHEET 2
  - CONNECTOR IS PART MARKED: 241□15690X CONEC ABC (see note 4)

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance	dim. in mm	scale: 2:1 (5:1)	
				date		name	material: SEE NOTES
				drawn	08.05.2014	Heinrich	title: <b>D-SUB C-FILTER MALE</b> 37pos. SOLDER PIN STRAIGHT
				appd.	08.05.2014	Henneboel	
			norm			dwg no: 24K1A1527 (b)	
			d-old	24K1A279/24K2A279			
			4 x b	A5200	08.05.14	Heinrich	DIN-A3
			a	Original			sh: 1/2
			rev.	description	date	name	part no: (b) 241□15690X (see note 4)