

For more Information  
please call

1-800-Belden1



## General Description:

Tinned copper conductor, PVC insulation. Use test probe leads for electrical and electronic measuring for test equipment.

## Physical Characteristics (Overall)

### Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 1            | 18  | 65x36     | TC - Tinned Copper |

Total Number of Conductors: 1

### Insulation

Insulation Material:

| Insulation Material      | Wall Thickness (mm) |
|--------------------------|---------------------|
| PVC - Polyvinyl Chloride | 1.2192              |

### Overall Insulation

#### Overall Cable

Overall Nominal Diameter: 3.658 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

|                                       |              |
|---------------------------------------|--------------|
| UL AWM Style:                         | 1855         |
| UL Rating:                            | 5000 V, 80°C |
| EU Directive 2011/65/EU (ROHS II):    | Yes          |
| EU CE Mark:                           | Yes          |
| EU Directive 2000/53/EC (ELV):        | Yes          |
| EU Directive 2002/95/EC (RoHS):       | Yes          |
| EU RoHS Compliance Date (mm/dd/yyyy): | 10/01/2005   |
| EU Directive 2002/96/EC (WEEE):       | Yes          |
| EU Directive 2003/11/EC (BFR):        | Yes          |
| CA Prop 65 (CJ for Wire & Cable):     | Yes          |
| MII Order #39 (China RoHS):           | Yes          |

### Plenum/Non-Plenum

Plenum (Y/N): No

## Electrical Characteristics (Overall)

Suggested Working Voltage: 5000 V RMS

## Put Ups and Colors:

| Item #       | Putup    | Ship Weight | Color       | Notes | Item Desc                  |
|--------------|----------|-------------|-------------|-------|----------------------------|
| 9899 002100  | 100 FT   | 2.100 LB    | RED         |       | #18 STR PVC TEST PROD RED  |
| 9899 0021000 | 1,000 FT | 15.000 LB   | RED         |       | #18 STR PVC TEST PROD RED  |
| 9899 002500  | 500 FT   | 7.500 LB    | RED         |       | #18 STR PVC TEST PROD RED  |
| 9899 005500  | 500 FT   | 7.500 LB    | GREEN, DARK |       | #18 STR PVC TEST PROD DGRN |
| 9899 009500  | 500 FT   | 7.500 LB    | WHITE       |       | 18 STR PVC TEST PROD WHT   |
| 9899 010100  | 100 FT   | 2.100 LB    | BLACK       |       | #18 STR PVC TEST PROD BLK  |
| 9899 0101000 | 1,000 FT | 15.000 LB   | BLACK       | C     | #18 STR PVC TEST PROD BLK  |
| 9899 010500  | 500 FT   | 7.500 LB    | BLACK       |       | #18 STR PVC TEST PROD BLK  |

### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 05-14-2007

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).