

## Active module - UMK 22 REL 24/21-21-ST (BASE) - 5529191

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE base module for G2R relay, 2PDT

### Product Features

- Relay base family that can be fitted with 2 PDT relay
- Safe isolation between coil and contact side
- For use with Omron G2R-2-S relays
- DIN rail mounting



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	41.0 GRM
Custom tariff number	85364190
Country of origin	United States

### Technical data

#### Dimensions

Width	22.5 mm
Height	77 mm
Depth with retaining bracket	50 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

#### Connection data

Conductor cross section solid min.	0.14 mm <sup>2</sup>
------------------------------------	----------------------

## Active module - UMK 22 REL 24/21-21-ST (BASE) - 5529191

### Technical data

#### Connection data

Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.14 mm <sup>2</sup>
Conductor cross section stranded max.	1.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	30
Conductor cross section AWG/kcmil max	14
Connection method	Screw connection
Stripping length	6 mm
Screw thread	M3

#### General

Nominal voltage U <sub>N</sub>	250 V AC/DC
Nominal current I <sub>N</sub>	5 A
Operating mode	100% operating factor
Mounting position	any
Assembly instructions	In rows with zero spacing

### Classifications

#### eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440401
eCl@ss 8.0	27440401

#### ETIM

ETIM 3.0	EC001604
ETIM 4.0	EC002498
ETIM 5.0	EC002498

#### UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121410
UNSPSC 13.2	39121421

