



LOC	DIST	ZONE	LTR	REVISIONS	DESCRIPTION	DATE	APPD
G	14		A	REVISED PER 0720-0230-93		2/28/94	DAF

METRIC
 DIMENSIONS LISTED IN MM [INCHES]

AMP WIRE RANGE 16-14 AWG STRANDED	UL E13288 Listed
LR7189 Certified	MILITARY P/N AND CLASS
NOT CERTIFIED	NOT APPLICABLE

△ STAMP AMP 16-14* APPROX AS SHOWN

AMP INCORPORATED
 CUSTOMER SERVICE SYSTEMS

FOR ADDITIONAL
 PRODUCT INFORMATION OR
 COPIES OF DRAWINGS
 AND TECHNICAL DOCUMENTS
 1-800-522-6752

FOR APPLICATION
 TOOLING INFORMATION
 1-800-722-1111

FOR ORDER ENTRY
 1-800-526-5142

MAX RECOMMENDED OPERATING
 TEMPERATURE:
 170°C MAX

VOLTAGE RATING:
 NOT APPLICABLE

WIRE CROSS SECTIONAL AREA RANGE:
 1.04-2.62mm² [2,050-5,180] CIR MILS
 STRANDED

DO NOT SCALE PRINT.
 UNLESS SPECIFIED
 DIMENSIONS IN mm [INCHES]
 TOLERANCES ON:
 1 PLC DEC ± .05
 2 PLC DEC ± .02
 3 PLC DEC ± .01
 ANGLES
 MATERIAL
 COPPER PER
 ASTM B-152
 ANNEALED

FINISH
 TIN PLATE
 0.00254 [L.000100] MIN
 THK PER MIL-T-10727

DR 3-3-93
 TA BRINKMAN

CHK 3-3-93
 DA PATTERSON

APPD 3-3-93
 DE MILLER

APPD 3-3-93
 JL NECKLEY

PRODUCT SPEC

AMP
 AMP Incorporated
 Harrisburg, PA 17105-3608

TERMINAL, FLANGED
 SPADE, BUDGET

SIZE CAGE CODE DRAWING NO
 00779 G-320854

SCALE 10:1

SHEET 1 OF 1