


CONFIGURAZIONE POLARIZZAZIONI  
POLARIZATION CONFIGURATION



- NOTE:
- USATO CON TERMINALE 94518-0XXX E 94549-0XXX
  - SPECIFICA DI RIFERIMENTO PER IL CONNETTORE PS-94550-001
  - PER CARATTERISTICHE DI CRIMPATURA RIF. SD-94518-005 E SD-94549-001
  - FORZA DI DISACCOPIAMENTO CONNETTORE (TRAZIONANDO DAI CAVI SENZA AZIONARE L'AGGANCIO): 40 N MIN.
  - SPESSORE MINIMO PARETI CONNETTORE 0.40 mm.

- NOTE:
- USED WITH TERMINALS 94518-0XXX AND 94549-0XXX
  - REFER TO PS-94550-001 FOR CONNECTOR SPECIFICATION
  - REFER TO SD-94518-005 AND SD-94549-001 FOR CRIMPING CHARACTERISTICS
  - CONNECTOR DISENGAGEMENT FORCE (PULLING BY THE WIRES, WITHOUT ACTUATING THE LATCH): 40 N MIN.
  - MINIMUM CONNECTOR WALL THICKNESS 0.40 mm.

P/N	MATERIAL/COLOR
94550-9103	NYLON 6.6 V0 NATURAL
94550-9193	NYLON 6.6 V0 GREY

CONFEZIONE: Box da 2200 Pz.  
PACKAGING: 2200 pcs in carton box

AGENCY  
RECOGNIZATIONS  
CSA (file LR19980)  
UL (file E-29179)

SPQ =2200

Std. Descr: "HSG W/SEC LOCK AND LATCH 3CKT \_\_\_\_\_ COLOR"

EC NO: Z2004-0206 DRWN: FGOTTARD 2004/05/12 CHKD: RSANDAN 2004/05/12 APPR: GZUIN 2004/05/13	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE 2:1	DESIGN UNITS METRIC	FIRST ANGLE PROJECTION	REVISE ON CAD ONLY	
		mm	INCH	DIMENSION STYLE MM ONLY		TITLE	
		4 PLACES ± --- ± ---		DRAWN BY DATE		HSG 3 CKT WITH SEC. LOCK AND EXTERNAL LATCH	
		3 PLACES ± --- ± ---		FGOTTARD 2003/05/06			
2 PLACES ± 0.10 ± ---		CHECKED BY DATE		MOLEX INCORPORATED			
1 PLACE ± 0.2 ± ---		APPROVED BY DATE				MATERIAL NO. DOCUMENT NO. SHEET NO.	
A1	REV	ANGULAR ± 2°	GZUIN 2003/05/06		SEE TABLE SD-94550-011 1 OF 1		
		DRAFT WHERE APPLICABLE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		A3		
		MUST REMAIN WITHIN DIMENSIONS					