

4

3

2

1

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN PERMISSION OF TALLYSMAN WIRELESS INC.

REVISIONS				
ZONE	REV	DESCRIPTION	DATE (DA-MO-YR)	APPROVED
	01	INITIAL RELEASE	2 NOV 12	M.G.
	02	CAP SCREWS ADDED	29 APR 13	M.G.

NOTES:

- UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETRES.
TOLERANCES:
1 DECIMAL PLACE ± 0.10
2 DECIMAL PLACES ± 0.05
ANGLES $\pm 1^\circ$
- TO CONVERT MILLIMETRES TO INCHES
USE 25.40 MILLIMETRES = 1 INCH.
- MATERIAL: ALUMINUM 6061-T6
- REMOVE ALL BURRS
- FINISH: BRUSH OUTSIDE SURFACE AS INDICATED
ANODIZE ARCHITCTUAL CLASE I A4I CLEAR
1.0 MIL MINIMUM ANODIC COATING.

$\varnothing 49$
 $\varnothing 18.2$
90°

BRUSH FINISH
16
25

$\varnothing 43.0$
22.0 DEEP

M4 X 0.7
2 PLACES

M4 X 6mm LONG CAP SCREW
STAINLESS STEEL
2 PLACES

THIRD ANGLE PROJECTION		Tallysman Wireless Inc.	
PMIC		PIPE MOUNT ADAPTER TW3000	
GEN. BY B DOLAN	DATE (Y-M-D) 25 OCT 12		
REVIEWED BY M GRINSTEAD			
PROJECT	SIZE C	CAGE CODE	DRAWING NUMBER 23-0065-0
NEXT ASSEMBLY	SCALE	UNIT WT	SHEET 1 OF 1

4

3

2

1

MODEL NAME 23-0065-0-02.PIPE-MOUNT