


TE Series

microSDXC Memory Card, Consumer plus MLC Model

■ **Product Outline**

TE series are microSDXC memory cards adopting built-in consumer type MLC NAND flash memory. They support U3 speed grade of UHS-I, and suitable for 4K video recording. They are formatted complying with SD card specification.

■ **Product Specification** (specifications and appearances may be changed without notice.)

| | | |
|--------------------------------|---------------------------------------|--|
| Appearance | | 64GB |
| | |  |
| Part Number | | RP-SMTE64DA1 |
| Capacity | Available user data area capacity *1) | 63,216,156,672 bytes |
| Compliant Specification | SD Physical Specification | Ver. 4.20 |
| | SD speed class | CLASS10 |
| | UHS speed grade | I U3 |
| | Speed mode | Default Speed Mode, High Speed Mode, SDR12/SDR25/SDR50/DDR50/SDR104 |
| Backside mark | Control Code | --- |
| Read/Write Performance (up to) | Read | 95MB/s (SDR104 mode) |
| | Write | 90MB/s (SDR104 mode) |
| Absolute Maximum Ratings | Supply Voltage | Min : -0.3 V ; Max : +4.6 V |
| | Input Voltage | Min : -0.3 V ; Max : VDD +0.3 V |
| | Output Voltage | Min : -0.3 V ; Max : VDD +0.3 V |
| | Output Current | Min : -24 mA ; Max : +24 mA |
| Environmental Specification | Operating Temperature | -25 degree C to +85 degree C |
| | Storage Temperature | -40 degree C to +85 degree C |
| | Humidity | 5 % RH to 95 % RH |
| | Vibration | 15 Gp-p |
| | Shock | 1,000 G |
| | Mating Cycles | 10,000 cycles |

*1) Free user area capacity after formatted.


Absolute Maximum Ratings are the values of limitation, which do not damage the card. So those values do not define the operational range.

Products comply with EU RoHS directives.

■ Marking Specification



“64GB” Card Capacity
 “MADE IN TAIWAN” Country of origin



“00000000” Internal control code
 “0000000000000000” Internal control code
 “00YM0000000” Serial Number
 Y Last digit of Manufacture year
 M Manufacture month
 (January->A, February->B,)

■ System Reliability

- a. Error detect and corrective function
- b. Static wear leveling
- c. Bad block management

■ Notice and Caution

If you think about the usage for which special quality or reliability of the products is needed and failure or malfunction of the products may directly threaten life or injury for the special usage (aeronautic or cosmic usage, military usage, combustion machine, life support applications or safety applications), please counsel with our contacts in advance.

Write frequency and storage temperature will affect data retention time. Please make a backup for important data.

■ Warranty

If the product cannot be used because of failure which is determined as defect in design or in production of the product, it is replaced by same product or equivalent one within 12 months from the delivery date of product.