

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	A	RELEASED PER ECO-14-006170	29APR2014	BY KAD
-	-	B	REVISED PER ECO-14-016601	04NOV2014	BY KPD
-	-	C	REVISED PER ECO-15-005560	06APR2015	DLB KAD

1. MATERIAL:
 BODY: ALUMINUM PER ASTM B317
 INSERT: BRASS PER ASTM B36

2. FINISH:
 BODY: .000600 MIN MATTE TIN PER ASTM B545
 OVER .000060 MIN NICKEL PER ASTM B733.
 INSERT: .000150 MIN MATTE NICKEL PER QQ-N-290

3 PTFE DRY LUBRICANT 360 DEGREE ON OUTER DIAMETER OF CRIMP BARREL IN ZONE SHOWN.

2102582-1

PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Brent D. Yohn 29APR2014	TE Connectivity	
DIMENSIONS: INCHES		CHK KIM DeBOCK 29APR2014		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD KIM DeBOCK 29APR2014	NAME ASSEMBLY, ALUMINUM TERMINAL, STRAIGHT, DOUBLE HOLE, 3/0	
0 PLC ±- 1 PLC ±.1 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0005 ANGLES ±1° FINISH		PRODUCT SPEC -	SIZE A200779	CAGE CODE C-2102582
MATERIAL SEE NOTE 1		APPLICATION SPEC -	DRAWING NO -	RESTRICTED TO -
SEE NOTE 2		WEIGHT -	SCALE 2:1	SHEET 1 OF 1
		Customer Drawing	REV C	

1471-9 (3/11)