

VIEW ON MATING SIDE

O	X	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	X				
D	Y	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	Y				
O	Z	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	Z					
	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1

A = 30 LMFB CONTACTS -0.6 L=3  
 B = 30 LMFB CONTACTS -0.6 L=3  
 C = 30 LMFB CONTACTS -0.6 L=3  
 Z = 2 STANDARD CONTACTS L=3  
 Y = 2 STANDARD CONTACTS L=3  
 X = 2 STANDARD CONTACTS L=3  
 S = 96 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G1/O = CONTACT AREA LEVEL I / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	YES
DIMENSIONS	SD-85003-0001 SHT I

X	G1/O	c1,32
Y	G1/O	b1,32
Z	G1/O	a1,32
C	G1/O	c2-31
B	G1/O	b2-31
A	G1/O	a2-31
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

ENTER DESCRIPTION EEC NO: 12005-02246 DRAWN BY: SIVAKUMA CHECKED BY: SSUDHIR APPR: KRAJSAJ DATE: 2004/11/02	QUALITY SYMBOLS 	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		4 PLACES ±--- ±--- 3 PLACES ±--- ±--- 2 PLACES ±--- ±--- 1 PLACE ±--- ±---	mm INCH	DRAWN BY SIVAKUMA	DATE 2004/11/02	TITLE 96 POS. MALE CONNECTOR ACC. DIN 41612 STYLE C CONTACTS ARRANGE			
		ANGULAR ±---°		CHECKED BY SSUDHIR	DATE 2004/11/02	APPROVED BY SSUDHIR			
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SIZE A 1	MATERIAL NO. 85003-9043	DATE 2004/11/02	DOCUMENT NO. SD-85003-9043	SHEET NO. 1 OF 1	MOLEX INCORPORATED	