




Contact No. 1



No. of Pin	Part. No.	A	B
4	DF11-4DP-2DSA(01)	6.0	2.0
6	DF11-6DP-2DSA(01)	8.0	4.0
8	DF11-8DP-2DSA(01)	10.0	6.0
10	DF11-10DP-2DSA(01)	12.0	8.0
12	DF11-12DP-2DSA(01)	14.0	10.0
14	DF11-14DP-2DSA(01)	16.0	12.0
16	DF11-16DP-2DSA(01)	18.0	14.0
18	DF11-18DP-2DSA(01)	20.0	16.0
20	DF11-20DP-2DSA(01)	22.0	18.0
22	DF11-22DP-2DSA(01)	24.0	20.0
24	DF11-24DP-2DSA(01)	26.0	22.0
26	DF11-26DP-2DSA(01)	28.0	24.0
28	DF11-28DP-2DSA(01)	30.0	26.0
30	DF11-30DP-2DSA(01)	32.0	28.0
32	DF11-32DP-2DSA(01)	34.0	30.0

Notes: The minimum ordering quantity for header is one package(containing 100 pieces).

- 2: Insulator : Nylon resin ,Black
- Contact Material: Brass
- Contact Plating : 0.2 μm gold plating

REVISIONS	BY	CHKD	DATE	REVISIONS	BY	CHKD	DATE
△							
△							
△							

No. MATERIAL APPROVED REVIEWED CHECKED DESIGNED DRAWN DRAWING No.	FINISH, REMARKS GENERAL DIMENSION TOLERANCE over 6 to 18 ±0.3 over 18 to 50 ±0.5 over 50 to 125 ±1 over 125 to 250 ±1.3 ANGULAR ±1°	No. MATERIAL FINISH, REMARKS GENERAL DIMENSION TOLERANCE over 6 to 18 ±0.3 over 18 to 50 ±0.5 over 50 to 125 ±1 over 125 to 250 ±1.3 ANGULAR ±1°	MATERIAL FINISH, REMARKS	APPROVED 14 January 20 20.8.29	FINISH, REMARKS ISSUED BY HRS HIROSE ELECTRIC CO., LTD. PART NO. DF11-8DP-2DSA(01) CODE NO.	
				REVIEWED		HRS HIROSE ELECTRIC CO., LTD. PART NO. DF11-8DP-2DSA(01) CODE NO.
				CHECKED		HRS HIROSE ELECTRIC CO., LTD. PART NO. DF11-8DP-2DSA(01) CODE NO.
				DESIGNED T.O.m.a. 90.8.29		HRS HIROSE ELECTRIC CO., LTD. PART NO. DF11-8DP-2DSA(01) CODE NO.
DRAWN T.O.m.a. 90.8.29	HRS HIROSE ELECTRIC CO., LTD. PART NO. DF11-8DP-2DSA(01) CODE NO.	HRS HIROSE ELECTRIC CO., LTD. PART NO. DF11-8DP-2DSA(01) CODE NO.	HRS HIROSE ELECTRIC CO., LTD. PART NO. DF11-8DP-2DSA(01) CODE NO.	HRS HIROSE ELECTRIC CO., LTD. PART NO. DF11-8DP-2DSA(01) CODE NO.	HRS HIROSE ELECTRIC CO., LTD. PART NO. DF11-8DP-2DSA(01) CODE NO.	
DRAWING No. EDC3-162393-01		UNITS mm SCALE 5:1		5 6 7 8 9 10 11 12		