



NOTES:

1. METALSHELLS: STEEL; min. 320µ" TIN
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. CONTACTS: COPPER ALLOY
4. PLATING: min. 8µ" HARD GOLD OVER min. 50µ" NICKEL
5. METAL BRACKET: STEEL; min. 320µ" TIN over 80µ" NICKEL
6. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
7. P.C.B. HOLE DRILLINGS ON DRAWING NO.: 16K111UA
8. CAPACITANCE: 2x1300pF ±20%
9. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
10. = CRITICAL DIMENSION: SPC

POS.	A	B	C	Part-NO.
9	31.19	16.46	25.00	242A26060X
15	39.52	24.79	33.30	242A26070X
25	53.42	38.50	47.04	242A26080X
37	69.70	54.96	63.50	242A26090X

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name

2001	date	name	tolerance
drawn	09.04.	Pareil	CONEC CORPORATION BRAMPTON, ONTARIO
appd.	09.04.	E. Mickenbecker	
norm	DIN 41852		
d-old			

scale:	2:1 (5:1)
material:	SEE NOTES
title:	D-SUB TT FILTER FEMALE 90° 0.590inch 9-37pos. with threaded insert and metal bracket
dwg no:	AutoCAD 2000 24K1A106A
part no:	DIN-A 3 sh:1/1



SEE TABLE