



General ordering data

Order No.	9506950000
Part designation	KST 8/35 M8X30
Version	Feed-through terminal, 35 mm ² , Screw connection, Polyamide, beige, TS 35
EAN	4008190425777
Qty.	25 pc(s).

Additional technical data

Colour of insulating material	beige
Connection direction	on side
End plate required	No
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	Polyamide
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	1
Open sides	Open
Operating temperature range	- 50 °C, + 100 °C
Type of connection	Screwed
Type of mounting	Clamped
UL 94 flammability rating of insulation material	V2
Version	Stud terminal

CSA rating data

Voltage (CSA)	600 V
CSA current	130 A
Min. cross-section (CSA)	AWG 12
Max. cross-section (CSA)	AWG 2

Conductors for clamping (rated connection)

Type of connection	Screw connection
Connection direction	on side
Tightening torque range	6.0...12 Nm

Dimensions

Width	24 mm
Height of lowest version	64.5 mm
Length	62.5 mm

Dimensions

Weight	76.8 g
TS 32 offset	14 mm
TS 35 offset	30 mm

Rating data

Rated cross-section	35 mm ²
Rated voltage	1,000 V
Rated impulse voltage	8 kV
Rated current	125 A
Current with max. conductor	125 A
Pollution severity	3

Stud connection

Stud size for spade connection	M 8
Tightening torque range	6.0...12 Nm

UL rating data

Voltage (UL)	600 V
Current (UL)	115 A
Min. cross-section (UL)	AWG 12
Max. cross-section (UL)	AWG 2

Approvals

Approvals institutes



Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Similar products

Order No.	Part designation	Version
9528330000	KST 10/35 M10X39	Feed-through terminal, 70 mm ² , Screw connection, Polyamide, beige, TS 35
9506960000	KST 10/35 M10X39	Feed-through terminal, 70 mm ² , Screw connection, Polyamide, beige, TS 35
9528340000	KST 12/35 M12X37	Feed-through terminal, 95 mm ² , Screw connection, Polyamide, beige, TS 35
9506970000	KST 12/35 M12X37	Feed-through terminal, 95 mm ² , Screw connection, Polyamide, beige, TS 35
9528300000	KST 5/35 M5X18	Feed-through terminal, 10 mm ² , Polyamide, beige, TS 35

9506940000	KST 6/35 M6X22	Feed-through terminal, 16 mm ² , Screw connection, Polyamide, beige, TS 35
9528320000	KST 8/35 M8X30	Feed-through terminal, 35 mm ² , Screw connection, Polyamide, beige, TS 35