

# FCC Part 15B TEST REPORT

**Product Name : GSM/GPRS Wireless Data Module**

**Model Name : SIM800H**

Prepared for:

**Shanghai Simcom Ltd.**

**Building A, SIM Technology Building, No.633, Jinzhong Road,  
Changning District, Shanghai P.R. China**

Prepared by:

**Unilab (Shanghai) Co., Ltd.**

**FCC 2.948 register number is 714465**

**No.1350, Lianxi Road, Pudong New District, Shangha, China**

**TEL: +86-21-5027 5125**

**FAX: +86-21-5027 5126**

**Report Number : UL15820130723FCC24-1**

**Date of Report : 2013-07-23**

**Date of Test : 2013-07-23~2013-07-26**

**Notes :**

The test results only relate to these samples which have been tested.

Partly using this report will not be admitted unless been allowed by Unilab.

Unilab is only responsible for the complete report with the reported stamp of Unilab.

**Applicant:** Shanghai Simcom Ltd.  
Building A, SIM Technology Building, No.633, Jinzhong Road,  
Changning District, Shanghai P.R. China

**Manufacturer:** Shanghai Simcom Ltd.  
Building A, SIM Technology Building, No.633, Jinzhong Road,  
Changning District, Shanghai P.R. China

**Product Name:** GSM/GPRS Wireless Data Module

**Brand Name:** SIMCom

**Model Name:** SIM800H

**Serial Number:** N/A

**FCC ID:** UDV-2013072401


**EUT Voltage:** AC input for adapter: AC 100~240V 50/60Hz  
Rated voltage: 3.6V~4.2V


**Date of Receipt:** 2013-07-23


**Test Standard:** FCC Part 15 Subpart B: 2010

**Test Result:** Complied

**Date of Test** 2013-07-23~2013-07-26

Prepared by :   
(Technical Engineer: Flame Wang)

Reviewed by :   
(Senior Engineer: Forest Cao)

Approved by :   
(Supervisor: Eva Wang)

## TABLE OF CONTENTS

<b>1.</b>	<b>TECHNIACL SUMMARY .....</b>	<b>4</b>
1.1	SUMMARY OF STANDARDS AND TEST RESULTS .....	4
1.2	TEST UNCERTAINTY .....	4
1.3	TEST EQUIPMENT LIST .....	4
1.4	SUPPORT EQUIPMENT .....	5
1.5	TEST FACILITY .....	5
1.6	TEST SETUP CONFIGURATION .....	5
<b>2.</b>	<b>CONDUCTED DISTURBANCE .....</b>	<b>6</b>
2.1	TEST SETUP .....	6
2.2	LIMITS .....	6
2.3	TEST PROCEDURE .....	6
2.4	TEST RESULT .....	7
<b>3.</b>	<b>RADIATED DISTURBANCE (RE) .....</b>	<b>9</b>
3.1	TEST SETUP .....	9
3.2	LIMITS .....	9
3.3	TEST PROCEDURE .....	10
3.4	TEST RESULT .....	11
<b>APPENDIX 1</b>	<b>PHOTOGRAPHS OF TEST SETUP.....</b>	<b>15</b>
<b>APPENDIX 2</b>	<b>PHOTOGRAPHS OF EUT .....</b>	<b>17</b>

## 1. TECHNICAL SUMMARY

### 1.1 SUMMARY OF STANDARDS AND TEST RESULTS

The EUT have been tested according to the applicable standards as referenced below:

EMISSION		
Test Item	Standard	Result
Conducted disturbance	FCC 15.107	P <sup>1</sup>
Radiated disturbance	FCC 15.109	P

Note1: P means pass, F means failure, N/A means not applicable

### 1.2 TEST UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Value (dB)
Conducted disturbance	3.4
Radiated disturbance	4.2

### 1.3 TEST EQUIPMENT LIST

Shielding Room No. 3 - Conducted disturbance Test				
Equipment	Manufacturer	Model	Serial No.	Due Date
Receiver	Agilent	N9038A	MY51210142	2013/09/28
LISN	R&S	ENV216	100069	2014/06/23

3m Semi-anechoic Chamber - Radiated disturbance Test				
Equipment	Manufacturer	Model	Serial No.	Due Date
3m Chamber & Accessory Equipment	ETS-LINDGREN	FACT-3	CT-0000336	2013/11/27
Receiver	Agilent	N9038A	MY51210142	2013/09/28
Biconilog Antenna	SCHWARZBECK	VULB 9160	3316	2013/09/20
Horn Antenna	SCHWARZBECK	BBHA9120D	00057407	2013/09/20
Microwave Preampfier	EM Electronics	EM30180	3008A02425	2014/03/01

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and has been calibrated by accredited calibration laboratories.

#### 1.4 SUPPORT EQUIPMENT

Equipment	Manufacturer	Model	Serial No.	Due Date
PC	DELL	VOSTRO 260	7JXLB3X	/
Displayer	DELL	E1910Hc	CN-0CD1MT-64180-OC7-06TS	/
Mouse	DELL	MS111-P	CN-0MF3JY-71581-2C7-05GB	/
Keyboard	DELL	KB212-B	CN-0Y88XT-65890-22L-01MG-A01	/
Adapter	JHC	JHC-A01-1A0	/	/

#### 1.5 TEST FACILITY

All test facilities used to collect the test data are located at No. 1350, Lianxi Rd. Pudong New District, Shanghai, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4, CISPR 16-1-1 and other equivalent standards. The laboratory is compliance with the requirements of the ISO/IEC/EN 17025.

#### 1.6 TEST SETUP CONFIGURATION

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.


##### **Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. All the tests were carried out with the EUT in normal operation. Which was shown in this test report is the worst test mode.

## 2. CONDUCTED DISTURBANCE

### 2.1 TEST SETUP

For mains port:



### 2.2 LIMITS

Limits for Class B digital devices

Frequency range (MHz)	Limits dB( $\mu$ V)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

**NOTE:** 1. The lower limit shall apply at the transition frequencies.  
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

### 2.3 TEST PROCEDURE

For mains port:

a. The EUT and support equipment were placed on a nonconductive table 0.8m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane. The EUT connected to the main through Line Impedance Stability Network (L.I.S.N) to provide a  $50 \Omega/50\mu\text{H}$  coupling impedance for the measuring equipment. The support equipment is also connected to the main power through a LISN that provides a  $50 \Omega/50\mu\text{H}$  coupling impedance with  $50 \Omega$  terminations. Both sides of AC line (Line & Neutral) were checked to find out the maximum conducted emission.


b. The RBW of the receiver was set at 9 kHz. The frequency range from 150 kHz to 30 MHz was checked. Run the receiver's pre-scan to record the maximum disturbance generated from EUT in all power lines in the full band.

c. For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

## 2.4 TEST RESULT


For mains port:

Test mode: Data exchange



Site : chamber  
 Condition : FCC P15 CLASS-B (QP) ENV216(N)-20120730 NEUTRAL  
 EUT : GSM/GPRS Wireless Data Module  
 Model Name : SIM800H  
 Temp/Humi : 24°C / 49%  
 Power Rating: AC 120V/60Hz  
 Mode : data exchange  
 Memo :

	Read Freq	Read Level	LISN Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.42	28.45	10.42	0.13	0.00	39.00	57.46	-18.46	Peak
2 pp	0.53	34.84	10.40	0.10	0.00	45.34	56.00	-10.66	Peak
3	1.18	26.09	10.31	0.14	0.00	36.54	56.00	-19.46	Peak
4	5.99	31.93	10.33	0.23	0.00	42.49	60.00	-17.51	Peak
5	12.52	27.46	10.47	0.34	0.00	38.27	60.00	-21.73	Peak
6	23.89	30.70	10.47	0.12	0.00	41.29	60.00	-18.71	Peak



Site : chamber  
 Condition : FCC P15 CLASS-B (QP) ENV216(L)-20120730 LINE  
 EUT : GSM/GPRS Wireless Data Module  
 Model Name : SIM800H  
 Temp/Humi : 24°C / 49%  
 Power Rating: AC 120V/60Hz  
 Mode : data exchange  
 Memo :


	Read Freq	LISN Level	LISN Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.43	25.47	10.55	0.13	0.00	36.15	57.20	-21.05	Peak
2 pp	0.54	30.42	10.53	0.11	0.00	41.06	56.00	-14.94	Peak
3	0.81	22.52	10.44	0.13	0.00	33.09	56.00	-22.91	Peak
4	6.12	34.05	10.48	0.24	0.00	44.77	60.00	-15.23	Peak
5	12.65	32.07	10.47	0.33	0.00	42.87	60.00	-17.13	Peak
6	23.89	30.65	10.48	0.12	0.00	41.25	60.00	-18.75	Peak




### 3. RADIATED DISTURBANCE (RE)

#### 3.1 TEST SETUP

30MHz ~ 1GHz:



Above 1GHz:



#### 3.2 LIMITS

Limits for Class B digital devices

Frequency (MHz)	limits at 3m dB(μV/m)
30-88	40.0
88-216	43.5
216-960	46.0
Above 960	54.0

- NOTE:**
1. The lower limit shall apply at the transition frequency.
  2. The limits shown above are based on measuring equipment employing a CISPR quasi-peak detector function for frequencies below or equal to 1000MHz.
  3. The limits shown above are based on measuring equipment employing an average detector function for frequencies above 1000MHz.

### 3.3 TEST PROCEDURE

#### 30MHz ~ 1GHz:

- a. The EUT and support equipment were placed on the non-conductive turntable 0.8m above the horizontal metal ground plane at a chamber. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. Broadband antenna (Calibrated Bilog Antenna) was used as receiving antenna.
- b. The frequency range from 30MHz to 1GHz was checked. The RBW of the receiver was set at 120kHz. Set the receiver in Peak detector, Max Hold mode. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- c. For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where EUT radiated the maximum emission, then set the test frequency receiver to QP Detector and record the maximum value.


#### Above 1GHz:

- a. The EUT and support equipment were placed on the non-conductive turntable 0.8m above the ground at a chamber. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. Horn antenna was used as receiving antenna.
- b. The frequency range above 1GHz was checked. The RBW of the receiver was set at 1MHz. Set the receiver in Peak detector, Max Hold mode. Record the maximum field strength of all the pre-scan process in the full band when the antenna is 1m and varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- c. For each frequency whose maximum record was higher or close to limit, measure its Average value: rotate the turntable from 0 to 360 degrees to find the degree where EUT radiated the maximum emission, then set the test frequency receiver to EMI Average Detector and record the maximum value.

### 3.4 TEST RESULT


#### 30MHz ~ 1GHz:

Test mode: Data exchange



Site : chamber  
 Condition : FCC CLASS-B 3m VULB9160 VERTICAL  
 EUT : GSM/GPRS Wireless Data Module  
 Model Name : SIM800H  
 Temp/Humi : 24°C / 49%  
 Power Rating: AC 120V/60Hz  
 Mode : Data exchange  
 Memo :

	ReadAntenna	Cable	Preamp	Limit	Over				
Freq	Level	Loss	Factor	Line	Limit	Remark			
MHz	dBm	dB/m	dB	dB	dBm/m	dBm/m			
1 pp	37.76	21.94	12.51	0.79	0.00	35.24	40.00	-4.76	Peak
2	187.14	17.35	11.55	1.88	0.00	30.78	43.50	-12.72	Peak
3	226.91	18.16	11.05	2.07	0.00	31.28	46.00	-14.72	Peak
4	384.05	13.70	14.97	2.74	0.00	31.41	46.00	-14.59	Peak
5	480.08	15.10	16.89	3.00	0.00	34.99	46.00	-11.01	Peak
6	647.89	13.06	19.56	3.53	0.00	36.15	46.00	-9.85	Peak




Site : chamber  
 Condition : FCC CLASS-B 3m VULB9160 HORIZONTAL  
 EUT : GSM/GPRS Wireless Data Module  
 Model Name : SIM800H  
 Temp/Humi : 24°C / 49%  
 Power Rating: AC 120V/60Hz  
 Mode : Data exchange  
 Memo :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
	MHz	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBm	dB/m	dB	dB	dBm/m	dBm/m	dB
1	38.73	14.44	12.61	0.81	0.00	27.86	40.00	-12.14 Peak
2	90.14	20.20	9.30	1.09	0.00	30.59	43.50	-12.91 Peak
3	143.49	16.22	13.58	1.62	0.00	31.42	43.50	-12.08 Peak
4 pp	180.35	19.37	12.22	1.88	0.00	33.47	43.50	-10.03 Peak
5	480.08	14.70	16.89	3.00	0.00	34.59	46.00	-11.41 Peak
6	756.53	10.09	21.36	3.74	0.00	35.19	46.00	-10.81 Peak


**Above 1GHz:**

Test mode: Data exchange



Site : chamber  
 Condition : FCC CLASS-B PK 3m BBHA9120D(942) HORIZONTAL  
 EUT : GSM/GPRS Wireless Data Module  
 Model Name : SIM800H  
 Temp/Humi : 24°C / 49%  
 Power Rating: AC 120V/60Hz  
 Mode : Data exchange  
 Memo :

	ReadAntenna	Cable	Preamp	Limit	Over			
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBm	dB/m	dB	dB	dBm/m	dBm/m	dB	
1	1289.00	50.93	25.52	5.20	38.43	43.22	74.00	-30.78 Peak
2	2513.00	47.89	27.57	7.36	38.30	44.52	74.00	-29.48 Peak
3	7885.00	38.69	36.96	12.83	39.38	49.10	74.00	-24.90 Peak
4	9874.00	36.50	38.69	14.63	39.62	50.20	74.00	-23.80 Peak
5 pp	11064.00	33.50	40.16	16.06	38.93	50.79	74.00	-23.21 Peak
6	14719.00	27.37	42.21	18.44	37.99	50.03	74.00	-23.97 Peak




Site : chamber  
 Condition : FCC CLASS-B PK 3m BBHA9120D(942) VERTICAL  
 EUT : GSM/GPRS Wireless Data Module  
 Model Name : SIM800H  
 Temp/Humi : 24°C / 49%  
 Power Rating: AC 120V/60Hz  
 Mode : Data exchange  
 Memo :


	ReadAntenna	Cable	Preamp		Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBm	dB/m	dB	dB	dBm/m	dBm/m	dB	
1	1595.00	55.89	24.98	5.71	38.46	48.12	74.00	-25.88 Peak
2	2173.00	48.90	27.81	6.79	38.43	45.07	74.00	-28.93 Peak
3	7086.00	36.82	35.96	12.57	36.60	48.75	74.00	-25.25 Peak
4	9653.00	35.65	38.14	14.69	40.02	48.46	74.00	-25.54 Peak
5	12050.00	31.90	39.35	16.66	39.35	48.56	74.00	-25.44 Peak
6 pp	14583.00	27.86	42.46	18.68	38.12	50.88	74.00	-23.12 Peak

## APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

### CONDUCTED DISTURBANCE TEST SETUP For power port



### RADIATED DISTURBANCE TEST SETUP 30M-1G



**Above 1G**





## APPENDIX 2 PHOTOGRAPHS OF EUT


View of EUT-1



View of EUT-2



View of EUT-3



View of EUT-4



