

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - BY - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD		
A		REVISED AND RELEASED PER ECO-14-005182	07APR2014	BY	KAD		
B		REVISED PER ECO-15-005560	06APR2015	DLB	KAD		

1. MATERIAL:
 BODY: ALUMINUM PER ASTM B317
 INSERT: BRASS PER ASTM B36

2. FINISH:
 BODY: .000600 MIN MATTE TIN PER ASTM B545
 OVER .000060 MIN NICKEL PER ASTM B733.
 INSERT: .000150 MIN MATTE NICKEL PER QQ-N-290

△ PTFE DRY LUBRICANT 360 DEGREE ON OUTER DIAMETER OF CRIMP BARREL IN ZONE SHOWN.

SCALE 1:1

SECTION C-C

2102579-1

PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Brent D. Yohn 07APR2014	TE Connectivity	
DIMENSIONS: INCHES		CHK K. A. DeBock 07APR2014		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD K. A. DeBock 07APR2014	NAME TERMINAL ASSEMBLY, STRAIGHT, ALUMINUM DUAL HOLE, SIZE 2 AWG	
0 PLC ±-		PRODUCT SPEC	SIZE	
1 PLC ±-		APPLICATION SPEC	CAGE CODE	
2 PLC ±.01		WEIGHT	DRAWING NO	
3 PLC ±.005		Customer Drawing	A2100779	
4 PLC ±-		SCALE 2:1	C-2102579	
ANGLES ±-		SHEET 1 OF 1	RESTRICTED TO	
FINISH		REV B		
SEE NOTES				

1471-9 (3/11)