



Part Number & Date Code Printing

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	PART NUMBER
09	30.81	24.99	16.96	16.21	D09S23B*PA00**
15	39.14	33.32	25.18	24.54	D15S23B*PA00**
25	53.03	47.04	39.12	38.25	D25S23B*PA00**
37	69.32	63.50	55.68	54.71	D37S23B*PA00**

LF FOR LEAD FREE

Plating: 4 --> flash AU
Plating: 6 --> 0.76µ AU

FOR ROHS DETAILS REFER DWG.NO:C01-8646-0000

REQUIREMENTS

Technical characteristics:
 Shell: steel tin/Zinc Cr3 plated
 Insulators: self-extinguishing thermoplastic, UL class 94V0
 Contacts size 20, phosphor bronze, gold on mating end, bright tin on termination end over nickel on entire contact

Cycles :500 for plating 6
 Cycles :200 for plating 4

Electrical characteristics:
 max. current rating: 5A
 Test voltage: 1000V
 Rated voltage: 300V
 Contact resistance: <15mΩ
 Shell resistance: <5mΩ
 Insulation resistance: >5000MΩ

Climatic characteristics:
 Operating temperature range: -55°C +125°C

Dimensions:
 In accordance with MIL-C-24308

European Views

www.fciconnect.com		surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection mm
TOLERANCES UNLESS OTHERWISE SPECIFIED				
Dr	JOHN SLEEBA	1996/09/24	ANGULAR	0.X ±0.1
Eng	GEORGE VJ	1996/09/24	LINEAR	0.XX ±0.1
Chr	GEORGE VJ	2005/07/27	0.XX* ±1*	0.XXX ±0.1
Appr	KVSD	2005/07/27	Product family	D-SUB
FCI		title SOCKET CONNECT.DELTA D right angle spill without accessories.		size A3
catalog no		DELTA-D		Scale 1:1
dwg no		C01-8646-0507		ECN -
CUSTOMER		sheet 1 of 1		Rev. C

rev	ecn no	dr	date
B	105-0124	JS	2005/07/27
C	106-0074	SK	2006/06/08
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Copyright FCI