


DESCRIPTION: 15 POS MICRO-D FEMALE (ASSEMBLED) TO BLUNT CUT



- 1. P1. CONNECTOR: NORCOMP MICRO D 15S, ASSEMBLED HOOD W/THUMBSCREWS
- 2. P2. BLUNT CUT END
- 3. WIRE: 28AWG [7X36] x15C +ALUMINUM FOIL W/BRAID 65%, UL2464, COLOR BLACK
- 4. PINDOUT:

P1	P2
1	BLACK
2	BROWN
3	RED
4	ORANGE
5	YELLOW
6	GREEN
7	BLUE
8	VIOLET
9	GRAY
10	WHITE
11	PINK
12	LIGHT GREEN
13	BLACK WHITE
14	BROWN WHITE
15	RED WHITE
SHELL	SHIELD

CCA-015-YYR152

I = INCHES LENGTH

F = FEET

M = METERS

EXAMPLES:

CCA-015-I18R152 = 18 INCHES

CCA-015-F03R152 = 3 FEET

CCA-015-M01R152 = 1 METER

PACKAGED: 1 PER BAG

RoHS COMPLIANT

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.		DRAWN: P. JENKINS	DATE: 01-18-12
	NorComp		CHECKED:	DATE:
SCALE: NTS			SHEET 1	OF 1
DWG NO.		CCA-015-YYR152		