

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION     | DATE      | DWN | APVD |
|---|-----|-----------------|-----------|-----|------|
|   | A   | INITIAL RELEASE | 08JUN2015 | DL  | CW   |
|   |     |                 |           |     |      |
|   |     |                 |           |     |      |

8-M3  
70  
7.8  
104  
148  
165  
27  
27  
96

(130.7)

4-Ø6.4  
70  
81  
117  
148

开孔安装示意图  
PANNEL CUT OUT

140.5  
132  
(149.1)  
5.2  
5  
10  
39.6  
4-Ø6.4  
4-Ø12.5

NOTES:

1. TECHNICAL CHARACTERISTICS:  
BODY MATERIAL: DIE CAST ALUMINIUM ALLOY  
SURFACE TREATMENT: POWDER-COATED, GRAY  
OPERATION TEMPERATURE: -40-+125°C  
DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:  
主体材料: 铝合金  
表面处理: 粉末喷涂, 灰色  
工作温度: -40-+125°C  
防护等级: IP65(配合)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN DAVID LI 08JUN2015

CHK CHRIS WANG 08JUN2015

APVD XU XIANG 08JUN2015

PRODUCT SPEC

108-137013

APPLICATION SPEC

114-137013

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME

H48B-AD-LB

SIZE

A3

CAGE CODE

-

DRAWING NO

C-TI510482000000

RESTRICTED TO

-

SCALE 1:2

SHEET 1 OF 1

REV A

TI510482000-000

H48B-AD-LB

ASSEMBLY PART  
NUMBERASSEMBLY PART  
DESCRIPTION

1470-19 (3/13)