

Specification Sheet

Part Number: GT.50X8MP2V2



Grip Tie, UL94V0-2 Flame Rated, .5" x 8.0", PA6/PP, Maroon, 10/pkg

Article Number

854-44368

Type

GT.50X8

Color

Maroon (MN)

Features & Benefits

- UL94V0-2 flame rate material allow use in air handling spaces.
- Features quick release for repetitive access to cable and wire.
- Can be opened and closed numerous times without failure.
- Adjustable so one size can accommodate multiple bundle sizes.

Quantity Per

bag

Product Description

The Grip Tie is a low profile, one piece fastening device. Constructed of polyethylene hook and nylon loop and laminated back to back, the Grip Tie features quick release for repetitive access to cable and wire. Grip Ties are available in a variety of colors and are versatile enough for applications ranging from network installations to bundling power cords.

Short Description

Grip Tie, UL94V0-2 Flame Rated, .5" x 8.0", PA6/PP, Maroon, 10/pkg

Global Part Name

GT.50X8

Minimum Tensile Strength (Imperial)

40.0

Minimum Tensile Strength (Metric)

177.93

Length L (Imperial)

8.0

Length L (Metric)

203.2

Width W (Imperial)

0.5

Width W (Metric)

12.7

Bundle Diameter Max (Imperial)

1.91

Bundle Diameter Max (Metric)

48.514

Material

Polyamide 6 (PA6) Polypropylene (PP)

Material Shortcut

PA6 PP

Package Quantity(Imperial)

10

Package Quantity (Metric)

10

Customs Number

9606100000

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)